

1. Product and company identification

Product name	: SCHÖNOX AP
Material uses	: Gypsum based levelling compound
Supplier	: HPS, Inc. 515 Wilhite Street Florence, AL 35630 USA
Manufacturer	: SCHÖNOX GmbH Alfred-Nobel-Straße 6 48720 Rosendahl Germany Phone: +49 (0) 2547 - 910-0 Fax: +49 (0) 2547 - 910-101 E-mail: info@schoenox.com
In case of emergency	: +49-170-2255126
National advisory body/Poison Centre	: Antipoison Center AAPCC (http://www.aapcc.org) +1 800 222 1222
Validation date	: 5/22/2012.
Print date	: 5/23/2012.
Product type	: Powder.

2. Hazards identification

Classification of the substance or mixture

Product definition : Mixture

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification : Not classified.

Label elements

Risk phrases : This product is not classified according to EU legislation.

Safety phrases : Not applicable.

Supplemental label elements : Safety data sheet available for professional user on request.

Other hazards which do not result in classification : Handling and/or processing of this material may generate a dust which can cause mechanical irritation of the eyes, skin, nose and throat.

Emergency overview

Physical state : Solid. [Powder.]

Colour : White. [Light]

Odour : Odourless. [Slight]

Signal word : WARNING!

Hazard statements : CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.

Precautionary measures : Use only with adequate ventilation. Do not eat, drink or smoke when using this product. Avoid contact with eyes, skin and clothing. Keep container tightly closed. Wash thoroughly after handling.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Potential acute health effects

Inhalation : Slightly irritating to the respiratory system.

Ingestion : No known significant effects or critical hazards.

Skin : Irritating to skin.

Eyes : Irritating to eyes.

Over-exposure signs/symptoms

2. Hazards identification

- Inhalation** : Adverse symptoms may include the following:
respiratory tract irritation
coughing
- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:
irritation
redness
- Eyes** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Medical conditions aggravated by over-exposure** : Pre-existing disorders involving any target organs mentioned in this MSDS as being at risk may be aggravated by over-exposure to this product.

See toxicological information (Section 11)

3. Composition/information on ingredients

Name	CAS number	%
calcium sulfate	7778-18-9	50 - 100
Limestone	1317-65-3	25 - 50
Quartz (SiO ₂)	14808-60-7	10 - 25
Cement, alumina, chemicals	65997-16-2	1 - 2,5

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

4. First-aid measures

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.
- Skin contact** : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.
- Inhalation** : Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.
- Ingestion** : Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

- Flammability of the product** : No specific fire or explosion hazard.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous thermal decomposition products** : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
metal oxide/oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Keep unnecessary and unprotected personnel from entering. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).
- Environmental precautions** : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods for cleaning up**
- Small spill** : Move containers from spill area. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labelled waste container. Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

- Handling** : Put on appropriate personal protective equipment (see Section 8). Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

8. Exposure controls/personal protection

Ingredient	Exposure limits
calcium sulfate	ACGIH TLV (United States, 2/2010). TWA: 10 mg/m ³ 8 hour(s). Form: Inhalable fraction
	NIOSH REL (United States, 6/2009). TWA: 5 mg/m ³ 10 hour(s). Form: Respirable fraction TWA: 10 mg/m ³ 10 hour(s). Form: Total
	OSHA PEL (United States, 6/2010). TWA: 5 mg/m ³ 8 hour(s). Form: Respirable fraction TWA: 15 mg/m ³ 8 hour(s). Form: Total dust
Limestone	NIOSH REL (United States, 6/2009). TWA: 5 mg/m ³ 10 hour(s). Form: Respirable fraction TWA: 10 mg/m ³ 10 hour(s). Form: Total
	OSHA PEL (United States, 6/2010). TWA: 5 mg/m ³ 8 hour(s). Form: Respirable fraction TWA: 15 mg/m ³ 8 hour(s). Form: Total dust
Quartz (SiO ₂)	OSHA PEL Z3 (United States, 9/2005). TWA: 10 mg/m ³ 8 hour(s). Form: Respirable TWA: 30 mg/m ³ 8 hour(s). Form: Total dust.
	ACGIH TLV (United States, 2/2010). Notes: Respirable fraction; see Appendix C, paragraph C. TWA: 0.025 mg/m ³ 8 hour(s). Form: Respirable fraction
	NIOSH REL (United States, 6/2009). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen TWA: 0.05 mg/m ³ 10 hour(s). Form: respirable dust

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
- Engineering measures** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

8. Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. Recommended: disposable particulate mask (FFP2)
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. 4-8 hours (breakthrough time): Nitrile gloves.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and chemical properties

- Physical state** : Solid. [Powder.]
- Colour** : White. [Light]
- Odour** : Odourless. [Slight]
- Relative density** : 1.02

10. Stability and reactivity

- Chemical stability** : The product is stable.
- Conditions to avoid** : No specific data.
- Incompatible materials** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.

11. Toxicological information

Acute toxicity

- Conclusion/Summary** : There are no data available on the preparation itself.

12. Ecological information

- Ecotoxicity** : No known significant effects or critical hazards.

Aquatic ecotoxicity

Product/ingredient name	Result	Species	Exposure
calcium sulfate	Acute LC50 >1910000 ug/L Fresh water	Daphnia - Ceriodaphnia dubia -	48 hours
	Acute LC50 >1970000 ug/L Fresh water	<24 hours Fish - Pimephales promelas - 1 to 7 days	96 hours

- Conclusion/Summary** : There are no data available on the preparation itself.

Persistence/degradability

- Conclusion/Summary** : There are no data available on the preparation itself.

13. Disposal considerations

Waste disposal : The generation of waste should be avoided or minimised wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-	-		-
ADR/RID Class	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

PG* : Packing group

15. Regulatory information

HCS Classification : Irritating material
Target organ effects

U.S. Federal regulations

TSCA : All ingredients appear on the Toxic Substance Control Act (TSCA) inventory or are not required to be listed.

SARA Title III Section 313 (40 CFR Part 372): : This product is not subject to SARA notification requirements and 40 CFR Part 372, since it not contain any Toxic Chemical constituents above the minimus concentrations.

State regulations

Massachusetts : The following components are listed: CALCIUM SULFATE; SILICA, CRYSTALLINE, QUARTZ; CALCIUM CARBONATE

New York : None of the components are listed.

New Jersey : The following components are listed: CALCIUM SULFATE; SULFURIC ACID, CALCIUM SALT (1:1); SILICA, QUARTZ; QUARTZ (SiO₂); CALCIUM CARBONATE; LIMESTONE

Pennsylvania : The following components are listed: CALCIUM SULFATE; QUARTZ (SiO₂); LIMESTONE

California Prop. 65 : **WARNING:** This product contains a chemical known to the State of California to cause cancer.
Quartz (SiO₂)

16. Other information

Label requirements : CAUSES EYE AND SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION. CONTAINS MATERIAL THAT MAY CAUSE TARGET ORGAN DAMAGE, BASED ON ANIMAL DATA.


Hazardous Material Information System (U.S.A.) :

Health	0
Flammability	0
Physical hazards	0

16. Other information

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

National Fire Protection Association (U.S.A.) :



Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Date of printing : 5/23/2012.

Date of issue : 5/22/2012.

Date of previous issue : 10/11/2011.

Version : 3

Prepared by : K.Hericks

▣ Indicates information that has changed from previously issued version.

Notice to reader

FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product. Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.



SCHÖNOX GmbH, Postbox 1140, D-48713 Rosendahl // <http://www.schoenox.de>